

27W / 2960lm / 2700K / DALI / Prismatic /
1149mm

61857



Design: Eduardo Souto de Moura
 Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.
 Prismatic polycarbonate diffuser with low luminance and glare control (UGR<19 for low output or UGR<22 for High Output).
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.
 Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
 Power supply included.
 IP40 | 230Vac | 50/60Hz



LED 2700K

Light Source Luminaire


Power 27W 32,9W

Flux 4780lm 2960lm

Efficiency 177lm/W 90lm/W

LOR - 62%

UGR - <22

Beam angle
Prismatic

Application

Weight
2,5Kg

mm

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium


Mandatory

54036 Pendant direct fitting accessory

56051 Clear Base DALI

ø60x35mm

For the specific supply of "DALI 2" drivers, please contact:
 support@om-light.com



Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
 supplemented by 2021/340/EU Energy Consumption Labelling
 Ordinance. This product contains light sources of efficiency class D
 Model Identifier 89603215