

14W / 1520lm / 3000K / On/Off / Prismatic /  
1149mm

61864




Design: Eduardo Souto de Moura  
 Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.  
 Prismatic polycarbonate diffuser with low luminance and glare control (UGR<19 for low output or UGR<22 for High Output).  
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.  
 Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
 Power supply included.  
 IP40 | 230Vac | 50/60Hz



	3000K	Light Source	Luminaire
Power	14W	17,1W	
Flux	2450lm	1520lm	
Efficiency	175lm/W	89lm/W	
LOR	-	62%	
UGR	-	<19	



Beam angle  
Prismatic



Application  
Weight  
2,5Kg

mm



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium

Mandatory

54036 Pendant direct fitting accessory  
 54034 Clear Base  
 ø60x35mm

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU  
 supplemented by 2021/340/EU Energy Consumption Labelling  
 Ordinance. This product contains light sources of efficiency class C  
 Model Identifier 89603216