

54W / 6080lm / 3000K / On/Off / Prismatic  
/ 2271mm

61869



Design: Eduardo Souto de Moura  
 Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.  
 Prismatic polycarbonate diffuser with low luminance and glare control (UGR<19 for low output or UGR<22 for High Output).  
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.  
 Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
 Power supply included.  
 IP40 | 230Vac | 50/60Hz



**LED** 3000K

**Light Source** Luminaire


**Power** 54W 63,5W

**Flux** 9800lm 6080lm

**Efficiency** 181lm/W 96lm/W

**LOR** - 62%

**UGR** - <22



**Beam angle**  
Prismatic



**Weight**  
5Kg

mm

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium

Mandatory

54036 Pendant direct fitting accessory

54034 Clear Base

ø60x35mm

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
 supplemented by 2021/340/EU Energy Consumption Labelling  
 Ordinance. This product contains light sources of efficiency class C  
 Model Identifier 89603216

