

34W / 3800lm / 3000K / DALI / Prismatic /  
2831mm

61878




Design: Eduardo Souto de Moura  
 Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.  
 Prismatic polycarbonate diffuser with low luminance and glare control (UGR<19 for low output or UGR<22 for High Output).  
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.  
 Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
 Power supply included.  
 IP40 | 230Vac | 50/60Hz



	<b>3000K</b>	<b>Light Source</b>	<b>Luminaire</b>
<b>Power</b>	<b>34W</b>	<b>40W</b>	
<b>Flux</b>	<b>6120lm</b>	<b>3800lm</b>	
<b>Efficiency</b>	<b>180lm/W</b>	<b>95lm/W</b>	
<b>LOR</b>	-	<b>62%</b>	
<b>UGR</b>	-	<b>&lt;19</b>	



Beam angle  
Prismatic



Weight  
6,2Kg

mm



#### Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium

#### Mandatory

54036 Pendant direct fitting accessory  
 56051 Clear Base DALI  
 ø60x35mm

For the specific supply of "DALI 2" drivers, please contact:  
 support@om-light.com

Data according to regulations  
 2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
 supplemented by 2021/340/EU Energy Consumption Labelling  
 Ordinance. This product contains light sources of efficiency class C  
 Model Identifier 89603211, 89603216