


7,9W / 670lm / 2700K / DALI / Diffuse /  
559mm

61912



**Structure**  
1 Profile  
2 End caps  
3 Fitting accessories  
4 Profile coupling

**Diffuser**  
A Polycarbonate frost diffuser  
**Light Source**  
B LED Modules

Design: O/M  
LED light source with good colour consistency and long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz




2700K

**Light Source**


**Luminaire**

<b>Power</b>	7,9W	9,9W
<b>Flux</b>	1400lm	670lm
<b>Efficiency</b>	177lm/W	68lm/W
<b>LOR</b>	-	48%
<b>UGR</b>	-	<25



**Beam angle**  
**Diffuse**

**Application**



**Weight**  
0,5Kg

mm

**Finishes**

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com

Choose the length and layout of the system exactly as you want it, to model the right lighting functions for different tasks. For further information please contact: support@om-light.com

**Data according to regulations**

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class D  
Model Identifier 89603215

