

34W / 2875lm / 2700K / DALI / Diffuse /
1399mm

61923

Design: O/M

LED light source with good colour consistency and long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP20 | 230Vac | 50/60Hz



Structure

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling

Diffuser

A Polycarbonate frost diffuser

Light Source

B LED Modules

| LED | 2700K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power | | 34W | 40W |
| Flux | | 5975lm | 2875lm |
| Efficiency | | 176lm/W | 72lm/W |
| LOR | | - | 48% |
| UGR | | - | <25 |



Beam angle
Diffuse

Application



Weight
0,58Kg



Finishes

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com

Choose the length and layout of the system exactly as you want it, to model the right lighting functions for different tasks. For further information please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C and D

Model Identifier 89603210, 89603215