


41W / 3450lm / 2700K / DALI + E-KIT /  
Diffuse / 1679mm

61927



**Structure**  
 1 Profile  
 2 End caps  
 3 Fitting accessories  
 4 Profile coupling

**Diffuser**  
 A Polycarbonate frost diffuser  
**Light Source**  
 B LED Modules

Design: O/M  
 LED light source with good colour consistency and long operation lifespan.


LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
 Power supply included.  
 IP20 | 230Vac | 50/60Hz



LED 2700K


Light Source Luminaire

Power	41W	48,2W
Flux	7170lm	3450lm
Efficiency	175lm/W	72lm/W
LOR	-	48%
UGR	-	<25



**Beam angle**  
**Diffuse**

**Application**



**Weight**  
**0,8Kg**

mm

**Finishes**

For the specific supply of "DALI 2" drivers, please contact:  
[support@om-light.com](mailto:support@om-light.com)

Choose the length and layout of the system exactly as you want it, to model the right lighting functions for different tasks. For further information please contact: [support@om-light.com](mailto:support@om-light.com)

**Data according to regulations**

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
 supplemented by 2021/340/EU Energy Consumption Labelling  
 Ordinance. This product contains light sources of efficiency class D  
 Model Identifier 89603215

