

76W / 5600lm / 3000K / DALI / Diffuse /  
2319mm

62036




Design: Eduardo Souto de Moura  
 Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.  
 Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.  
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.  
 Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
 Power supply included.  
 IP40 | 230Vac | 50/60Hz



LED	3000K	Light Source	Luminaire
Power	76W	89,4W	
Flux	9040lm	5600lm	
Efficiency	119lm/W	63lm/W	
LOR	-	62%	
UGR	-	<25	



Beam angle  
Diffuse





Weight  
10,4Kg

2319 mm

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium



Mandatory

54036 Pendant direct fitting accessory  
 56051 Clear Base DALI  
 ø60x35mm

For the specific supply of "DALI 2" drivers, please contact:  
 support@om-light.com

Data according to regulations  
 2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
 supplemented by 2021/340/EU Energy Consumption Labelling  
 Ordinance. This product contains light sources of efficiency class D  
 Model Identifier WU-M-536-S-BC-830