

70W / 6200lm / 4000K / On/Off / Diffuse /
1173mm

62041




Design: Eduardo Souto de Moura
 Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.
 Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.
 Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
 Power supply included.
 IP40 | 230Vac | 50/60Hz



LED	4000K	Light Source	Luminaire
Power	70W	82,4W	
Flux	10000lm	6200lm	
Efficiency	143lm/W	75lm/W	
LOR	-	62%	
UGR	-	<25	




Beam angle
Diffuse



Weight
5,2Kg

mm



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium

Mandatory

54036 Pendant direct fitting accessory
 54034 Clear Base
 ø60x35mm

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
 supplemented by 2021/340/EU Energy Consumption Labelling
 Ordinance. This product contains light sources of efficiency class C
 Model Identifier WU-M-536-S-BC-840