

140W / 12400lm / 4000K / DALI / Diffuse /
2319mm

62053




Design: Eduardo Souto de Moura
 Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.
 Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.
 Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
 Power supply included.
 IP40 | 230Vac | 50/60Hz



LED	4000K	Light Source	Luminaire
Power	140W	161W	
Flux	20000lm	12400lm	
Efficiency	143lm/W	77lm/W	
LOR	-	62%	
UGR	-	<25	





Beam angle
Diffuse



Weight
10,4Kg

mm



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium

Mandatory

54036 Pendant direct fitting accessory
 56051 Clear Base DALI
 ø60x35mm

For the specific supply of "DALI 2" drivers, please contact:
 support@om-light.com

Data according to regulations
 2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
 supplemented by 2021/340/EU Energy Consumption Labelling
 Ordinance. This product contains light sources of efficiency class C
 Model Identifier WU-M-536-S-BC-840