

U120
IP54 Recessed

95W / 7000lm / 3000K / On/Off / Diffuse /
2895mm

62062



Design: Eduardo Souto de Moura
Recessed luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.
Frosted polycarbonate diffuser with user friendly clipping system.
Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.
Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP54 | 230Vac | 50/60Hz



LED	3000K	Light Source	Luminaire
Power		95W	109W
Flux		11300lm	7000lm
Efficiency		119lm/W	64lm/W
LOR		-	62%
UGR		-	<25



Beam angle
Diffuse


Application



Weight
13Kg



122x2885



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium

Mandatory

53080 Recessed fitting accessory

O/M recommends that any false ceilings intended for recessed products should be installed only after the products to be used have been chosen. The same applies when preparing openings for this type of product. O/M recommends reinforcing false ceilings close to any such openings, in accordance with the characteristics of the product to be recessed. The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class D
Model Identifier WU-M-526-S-BC-830, WU-M-536-S-BC-830