

76W / 5600lm / 3000K / DALI / Diffuse /
2319mm

62100



Design: Eduardo Souto de Moura
 Surface luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.
 Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
 Power supply included.
 IP54 | 230Vac | 50/60Hz



LED 3000K

Light Source Luminaire


Power 76W 89,4W

Flux 9040lm 5600lm

Efficiency 119lm/W 63lm/W

LOR - 62%

UGR - <25



Beam angle
Diffuse





Weight
10,4Kg

mm

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com



Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
 supplemented by 2021/340/EU Energy Consumption Labelling
 Ordinance. This product contains light sources of efficiency class D
 Model Identifier WU-M-536-S-BC-830