

76W / 6640lm / 4000K / On/Off / Diffuse /
2319mm

62108



Design: Eduardo Souto de Moura
 Surface luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint.
 Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.
 Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
 Power supply included.
 IP54 | 230Vac | 50/60Hz



4000K

Light Source

Luminaire


Power **76W** **89,4W**

Flux **10720lm** **6640lm**

Efficiency **141lm/W** **74lm/W**

LOR **-** **62%**

UGR **-** **<25**



Beam angle
Diffuse



Weight
10,4Kg

mm

Finishes

- .01 White / RAL 9010**
- .02 Black / RAL 9005**
- .10 Anodised aluminium**

Data according to regulations
 2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
 supplemented by 2021/340/EU Energy Consumption Labelling
 Ordinance. This product contains light sources of efficiency class C
 Model Identifier WU-M-536-S-BC-840

