

H45 Pendant

20+9W / 1675+700lm / 3000K / On/Off / Diffuse / batwing / 1429mm

62186



Design: O/M


Pendant direct and indirect light luminaire with housing made of anodised aluminium profile with textured paint finish. Frosted diffuser for direct light and clear diffuser for indirect light with user friendly clipping system. 5mm aluminium end caps. Separate Circuits.

Suspension accessories available separately. Supply base made of aluminium, clear power cable (3x0,75mm²) and steel suspension cables (1,5mm) with millimetric height adjustment system.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP20 | 230Vac | 50/60Hz



	Light Source	Luminaire
Power	20+9W	24,4+11,3W
Flux	3575+1100lm	1675+700lm
Efficiency	157lm/W	64lm/W
LOR	-	51%
UGR	-	<22




Beam angle Diffuse / batwing

Application



Weight 4,9Kg

mm



Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

.10 Anodised aluminium

Mandatory

56053 Pendant direct/indirect fitting acessory **54034** Clear base Ø60x35mm

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C and E

Model Identifier 89603211, 89603216, WU-M-594-830