

## **H45 Pendant**

68+50W / 5750+3450Im / 3000K / DALI / Diffuse / batwing / 2831mm

62199



Design: O/M


Pendant direct and indirect light luminaire with housing made of anodised aluminium profile with textured paint finish. Frosted diffuser for direct light and clear diffuser for indirect light with user friendly clipping system. 5mm aluminium end caps. Separate Circuits.

Suspension accessories available separately. Supply base made of aluminium, clear power cable (3x0,75mm²) and steel suspension cables (1,5mm) with millimetric height adjustment system.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP20 | 230Vac | 50/60Hz



	Light Source	Luminaire
Power	68+50W	80+58,8W
Flux	12250+5500lm	5750+3450lm
Efficiency	150lm/W	66lm/W
LOR	-	52%
UGR	-	<25




Beam angle Diffuse / batwing

Application



Weight

1 3	



## Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

.10 Anodised aluminium

## Mandatory

56053 Pendant direct/indirect fitting acessory 56051 Clear base DALI Ø60x35mm

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

## Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C

Model Identifier WU-M-594-830, 89603216