

## H45 Made-to-measure

16+9W / 1340+700lm / 3000K / On/Off /  
Diffuse / batwing / 1119mm

62302

Design: O/M

LED light source with good colour consistency and long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz



### Structure

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling

### Diffuser

A Polycarbonate frost diffuser

### Light Source

B LED Modules

LED	3000K	Light Source	Luminaire
Power		16+9W	19,5+11,3W
Flux		2860+1100lm	1340+700lm
Efficiency		156lm/W	65lm/W
LOR		-	51%
UGR		-	<22



Beam angle  
Diffuse / batwing

Application



Weight  
0,5Kg



### Finishes

Choose the length and layout of the system exactly as you want it, to model the right lighting functions for different tasks. For further information please contact: [support@om-light.com](mailto:support@om-light.com)

### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C and E

Model Identifier WU-M-594-830, 89603216

