

H45

Made-to-measure

34+20W / 2875+1380lm / 3000K / On/Off /
Diffuse / batwing / 1399mm

62305

Design: O/M

LED light source with good colour consistency and long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP20 | 230Vac | 50/60Hz



Structure

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling

Diffuser

A Polycarbonate frost diffuser

Light Source

B LED Modules

LED	3000K	Light Source	Luminaire
Power		34+20W	40+24,4W
Flux		6125+2200lm	2875+1380lm
Efficiency		154lm/W	66lm/W
LOR		-	51%
UGR		-	<25



Beam angle
Diffuse / batwing

Application



Weight
0,51Kg



Finishes

Choose the length and layout of the system exactly as you want it, to model the right lighting functions for different tasks. For further information please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C and E

Model Identifier 89603211, 89603216, WU-M-594-830

