

Tubo Evo

20W / 1440lm / 3000K / DALI / Flood 46° / 535mm

62459



Design: O/M

Surface luminaire with tubular shock-resistant clear polycarbonate diffuser and anti-condensation system comprising a valve that prevents condensation within the luminaire without affecting its high level of protection.

End caps in clear polycarbonate with marked installation angles.

Optic system with acrylic lens.


Equipped with 1m cable (H05RN-F) and a metallic cable gland.

Fitting accessories and IP68 connector supplied separately.

LED CRI>90 />50.000h, L80/B10 / 3-step MacAdam Power supply included. IP67 | IK08| 230Vac | 50/60Hz



| 1000K | Light Source | Luminaire |
|------------|--------------|-----------|
| Power | 20W | 24,4W |
| Flux | 1930lm | 1440lm |
| Efficiency | 97lm/W | 59lm/W |
| LOR | - | 75% |
| UGR | - | <13 |
| | | |



Beam angle Flood 46°

Application



Weight 0,5Kg

| =i, | nis | h | 20 | |
|-----|-----|---|----|--|

.20 Clear

Mandatory

43431 IP68 Connector

43707 Surface fitting acessory

5 poles

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com





mm