

## Tubo 70

32W / 4360lm / 4000K / On/Off / Diffuse / 2312mm

62644



Design: Eduardo Souto de Moura

Surface or pendant luminaire with tubular shock-resistant frosted polycarbonate body with 70mm diameter.

Clear polycarbonate end caps with marked installation angles. Supplied with 30mm plastic cable gland that

prevents condensation within luminaire.

Fitting accessories ordered separately.


LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam

Power supply included.

IP67 | IK08 | 230Vac | 50/60Hz



LED	4000K	Light Source	Luminaire
Power		32W	37,6W
Flux		6040lm	4360lm
Efficiency		189lm/W	116lm/W
LOR		-	72%
UGR		-	<25



Beam angle  
Diffuse

Application



Weight  
2,6Kg

mm



Finishes

● .25 Frost

Mandatory

43708 Surface fitting accessory (>2000mm)

43710 Pendant fitting accessory (>2000mm)

Optional

59062 Stainless steel fitting accessory (>2000mm)

59059 Wall fitting accessory

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class B Model Identifier 28004774