

32W / 4040lm / 2700K / On/Off / Diffuse /
2312mm


62660



Design: Eduardo Souto de Moura

Surface or pendant luminaire with tubular shock-resistant frosted polycarbonate body with 70mm diameter.

Clear polycarbonate end caps with marked installation angles. Supplied with 30mm plastic cable gland that prevents condensation within luminaire. Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included.
IP67 | IK08 | 230Vac | 50/60Hz
2700K
Light Source **Luminaire**
Power **32W** **37,6W**
Flux **5600lm** **4040lm**
Efficiency **175lm/W** **107lm/W**
LOR **-** **72%**
UGR **-** **<25**

Beam angle
Diffuse
Application

Weight
2,6Kg
mm
Finishes
.25 Frost
Mandatory
43708 Surface fitting accessory (>2000mm)

43710 Pendant fitting accessory (>2000mm)

Optional
59062 Stainless steel fitting accessory (>2000mm)

59059 Wall fitting accessory

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU

supplemented by 2021/340/EU Energy Consumption Labelling

Ordinance. This product contains light sources of efficiency class C

Model Identifier 28004771

