

32W / 4120lm / 3000K / On/Off / Diffuse /  
2312mm

62676



Design: Eduardo Souto de Moura

Surface or pendant luminaire with tubular shock-resistant frosted polycarbonate body with 70mm diameter.

Clear polycarbonate end caps with marked installation angles. Supplied with 30mm plastic cable gland that prevents condensation within luminaire. Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included.  
IP67 | IK08 | 230Vac | 50/60Hz

**LED** 3000K

**Light Source** **Luminaire**


**Power** **32W** **37,6W**

**Flux** **5720lm** **4120lm**

**Efficiency** **179lm/W** **109lm/W**

**LOR** - **72%**

**UGR** - **<25**



**Beam angle**  
**Diffuse**



**Weight**  
**2,6Kg**

**mm**

**Finishes**

**.25 Frost**

**Mandatory**

**43708** Surface fitting accessory (>2000mm)

**43710** Pendant fitting accessory (>2000mm)

**Optional**

**59062** Stainless steel fitting accessory (>2000mm)

**59059** Wall fitting accessory

**Data according to regulations**

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU

supplemented by 2021/340/EU Energy Consumption Labelling

Ordinance. This product contains light sources of efficiency class C  
Model Identifier 28004772

