

## Dot Ground / Concrete

2,2W / 180lm / 3000K / On/Off / Flood 41° / Ø36mm

62729



Design: O/M

Ground-recessed luminaire made of anodised aluminium body with 25-micron maximum corrosion resistance anodization and frame in aluminium matt finish.

Tempered clear glass diffuser.


Recessed housing and driver supplied separately.

Values for 700mA. For 350mA estimate half of the indicated values.

LED CRI>90 / >50.000h, L80/B10 / 3-step MacAdam  
IP67 | 350mA / 700mA



LED	3000K	Light Source	Luminaire
Power		2,2W	2,2W
Flux		215lm	180lm
Efficiency		98lm/W	82lm/W
LOR		-	84%
UGR		-	<22




Beam angle  
Flood 41°

Application



Weight  
0,07Kg



## Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .12 Brushed stainless steel
- .34 Rust

## Mandatory

**27396** Recessed housing  
Ø32x80mm

**59124** 15W Driver

1 to 10 luminaires / 350mA

**59125** 8W Driver

1 to 5 luminaires / 350mA

**59126** 15W Driver

1 to 10 luminaires / 350mA

**59127** 25W Driver

5 to 18 luminaires / 350mA

**59128** 11W Driver

1 to 4 luminaires / 700mA

**59129** 35W Driver

1 to 12 luminaires / 700mA

**59130** 17W Driver

1 to 5 luminaires / 700mA

**59131** 48W Driver

1 to 18 luminaires / 700mA

## Optional

**27400** IP68 Connector 2 way

4 poles

**27395** IP68 Pass-through wiring connection box

3 way

**59052** Spike for ground/garden application