

18W / 1440lm / 2200K / Medium 30° /
1165mm

62772



Design: O/M

Module with housing made of aluminium profile with integrated LED light source and frosted acrylic diffuser.

Includes cable to connect modules with male and female plug connector.

Components supplied separately: power supply, DALI dimmer, power cable, extension cable and fitting accessories 45°.

Maximum length of the sum of the modules: $\leq 4m$.

LED CRI>80 / >50.000h, L80/B50 / 3-step MacAdam.
IP44 | 48Vdc



| LED | 2200K | Light Source | Luminaire |
|------------|--------|--------------|-----------|
| Power | 18W | 18W | 18W |
| Flux | 1760lm | 1440lm | 1440lm |
| Efficiency | 98lm/W | 80lm/W | 80lm/W |
| LOR | - | - | 82% |
| UGR | - | - | - |




Beam angle
Medium 30°

Application



Weight
0,35Kg

mm



Finishes

● .25 Frost

Included

Fitting accessories 0°
34x19x7mm

Mandatory

18105 Power cable

2x0,35mm² (0,5m)

18106 Power cable

2x0,35mm² (1m)

18820 Power Supply 16W

On/Off

18821 Power Supply 30W

On/Off

18822 Power Supply 55W

On/Off

18823 Power Supply 75W

On/Off

18824 Power Supply 150W

On/Off

18833 LED Dimmer DALI

Optional

18107 Extension cable

2x0,35mm² (1m)

18108 Extension cable

2x0,35mm² (5m)

18831 Fitting accessories 45°

45x19,5x20mm