


34W / 3800lm / 3000K / On/Off / Prismatic /  
1399mm

63009



Structure	Diffuser
1 Profile	A Polycarbonate frost
2 End caps	diffuser
3 Fitting accessories	
4 Profile coupling	B LED Modules

Design: O/M

LED light source with good colour consistency and long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz




3000K

**Light Source**


**Luminaire**

<b>Power</b>	<b>34W</b>	<b>40W</b>
<b>Flux</b>	<b>6125lm</b>	<b>3800lm</b>
<b>Efficiency</b>	<b>180lm/W</b>	<b>95lm/W</b>
<b>LOR</b>	<b>-</b>	<b>62%</b>
<b>UGR</b>	<b>-</b>	<b>&lt;22</b>



**Beam angle**  
**Prismatic**

**Application**



**Weight**  
**0,58Kg**

mm

**Finishes**

Choose the length and layout of the system exactly as you want it, to model the right lighting functions for different tasks. For further information please contact: support@om-light.com

**Data according to regulations**

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains light sources of efficiency class C  
Model Identifier 89603211, 89603216

