

## U60

### Made-to-measure

20W / 2415lm / 4000K / On/Off / Prismatic /  
839mm

63037

Design: O/M

LED light source with good colour consistency and long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz



#### Structure

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling

#### Diffuser

- A Polycarbonate frost diffuser

#### Light Source

- B LED Modules

| LED        | 4000K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power      |       | 20W          | 24,4W     |
| Flux       |       | 3900lm       | 2415lm    |
| Efficiency |       | 195lm/W      | 99lm/W    |
| LOR        |       | -            | 62%       |
| UGR        |       | -            | <22       |



Beam angle  
Prismatic

Application



Weight  
0,51Kg



#### Finishes

Choose the length and layout of the system exactly as you want it, to model the right lighting functions for different tasks. For further information please contact: [support@om-light.com](mailto:support@om-light.com)

#### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C  
Model Identifier 89603212, 89603217

