

U60 Made-to-measure

27W / 3220Im / 4000K / DALI / Prismatic / 1119mm

63055



LED light source with good colour consistency and long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included. IP20 | 230Vac | 50/60Hz



| 9 | 0 0 | |
|---|------------|-----------------------|
| | Structure | Diffuser |
| | 1 Profile | A Polycarbonate frost |
| | 2 End caps | diffuser |


Light Source

B LED Modules

3 Fitting accessories

4 Profile coupling

| 1000K | Light Source | Luminaire |
|------------|--------------|-----------|
| Power | 27W | 32,9W |
| Flux | 5200lm | 3220lm |
| Efficiency | 193lm/W | 98lm/W |
| LOR | - | 62% |
| UGR | - | <22 |




Prismatic Application

Beam angle



Weight 0,57Kg





Finishes

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

Choose the length and layout of the system exactly as you want it, to model the right lighting functions for different tasks. For further information please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C Model Identifier 89603217