

41W / 5610lm / 4000K / On/Off / Diffuse /  
1752mm

63087



Design: Eduardo Souto de Moura

Surface or pendant luminaire with tubular shock-resistant frosted polycarbonate body with 70mm diameter.

Clear polycarbonate end caps with marked installation angles. Supplied with 30mm plastic cable gland that prevents condensation within luminaire. Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam Power supply included.  
IP67 | IK08 | 230Vac | 50/60Hz

**4000K**

**Light Source** **Luminaire**


**Power** **41W** **48,2W**

**Flux** **7800lm** **5610lm**

**Efficiency** **190lm/W** **116lm/W**

**LOR** **-** **72%**

**UGR** **-** **<28**



**Beam angle**  
**Diffuse**

**Application**



**Weight**  
**1,7Kg**

**mm**

**Finishes**

**.25 Frost**

**Mandatory**

**43707 Surface fitting accessory**

**43709 Pendant fitting accessory**

**Optional**

**59058 Stainless steel fitting accessory**

**59059 Wall fitting accessory**

**Data according to regulations**

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU

supplemented by 2021/340/EU Energy Consumption Labelling

Ordinance. This product contains light sources of efficiency class B  
Model Identifier 28004774

