



10W / 760lm / 3000K / On/Off / Medium 23° / ø75mm

63192



Ceiling-recessed luminaire made of aluminium die-


Adjustable version (orientable by 30° on the horizontal axis and 355° on the vertical axis). Recessing accessory for flush version supplied separately.

LED CRI>90 / >50.000h, L80/B10 2-step MacAdam / Power supply included. IP20 | 230Vac | 50/60Hz



•

3000K	Light Source	Luminaire
Power	10W	12,5W
Flux	1035lm	760lm
Efficiency	104lm/W	61lm/W
LOR	-	73%
UGR	-	<19



Beam angle Medium 23°


Application



Weight 0,38Kg

mm

@070 (trim version)



Finishes

O .04 Matt White

.05 Matt Black

Optional

59063 Flush accessory (12.5mm ceilings)

176×17mm

59064 Flush accessory (15mm ceilings)

176×19,5mm

59065 Flush accessory (25mm ceilings)

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class $\ensuremath{\mathsf{F}}$ Model Identifier 2053560257H