



Beam Adjustable

4,5W / 390lm / 3000K / DALI / Flood 37° / ø75mm

63198



Ceiling-recessed luminaire made of aluminium die-


Adjustable version (orientable by 30° on the horizontal axis and 355° on the vertical axis). Recessing accessory for flush version supplied separately.

LED CRI>90 / >50.000h, L80/B10 2-step MacAdam / Power supply included. IP20 | 230Vac | 50/60Hz





| ● 3000K | Light Source | Luminaire |
|------------|--------------|-----------|
| Power | 4,5W | 5,8W |
| Flux | 520lm | 390lm |
| Efficiency | 116lm/W | 68lm/W |
| LOR | - | 75% |
| UGR | - | <19 |



Beam angle Flood 37°


Application



Weight 0,38Kg



@070 (trim version)



Finishes

O .04 Matt White

.05 Matt Black

Optional

59063 Flush accessory (12.5mm ceilings)

176×17mm

59064 Flush accessory (15mm ceilings) 176×19,5mm

59065 Flush accessory (25mm ceilings)

176×29,5mm

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

The cutout dimensions are for plasterboard ceilings. For other type of $material\ please\ contact: support@om-light.com$

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class $\ensuremath{\mathsf{F}}$ Model Identifier 2053560257L