



10W / 1150lm / 4000K / DALI / Flood 46° / ø100mm

63232



Ceiling-recessed luminaire made of aluminium die-


Adjustable version (orientable by 30° on the horizontal axis and 355° on the vertical axis). Recessing accessory for flush version supplied separately.

LED CRI>80 / >50.000h, L80/B10 3-step MacAdam / Power supply included. IP20 | 230Vac | 50/60Hz



-	•
•	•

1000K	Light Source	Luminaire
Power	10W	12,5W
Flux	1450lm	1150lm
Efficiency	145lm/W	92lm/W
LOR	-	79%
UGR	-	<22




Beam angle Flood 46° Application

Weight

mm

@095 (trim version)



Finishes

O .04 Matt White

.05 Matt Black

Optional

59066 Flush accessory (12.5mm ceilings)

201×17mm

59067 Flush accessory (15mm ceilings)

201×19,5mm

59068 Flush accessory (25mm ceilings)

201×29,5mm

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

The cutout dimensions are for plasterboard ceilings. For other type of $material\ please\ contact: support@om-light.com$

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class E Model Identifier BXRC-40E2000-C-73