


13W / 910lm / 2700K / DALI / Flood 52° /
300mm

63349



Design: O/M + Bartenbach GmbH

Luminaire with housing of aluminium profile with electrostatic 100% polyester paint with textured-finish.

Focal-lens with complex surface and individual complex surface rips to provide a focal point through an aperture for glare free area illumination.

Special springs available on request.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam
Power supply included.
IP20 | 230Vac | 50/60Hz

LED 2700K

Light Source**Luminaire**


Power 13W 15,9W

Flux 1200lm 910lm

Efficiency 92lm/W 57lm/W

LOR - 76%

UGR - <16




Beam angle
Flood 52°

Application

Weight
0,3Kg

Image not found or type unknown

**Finishes**

- .01** White / RAL 9010
- .02** Black / RAL 9005

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class F
Model Identifier 4053560342H