



## One **Asymmetric**

5,9W / 630lm / 4000K / DALI / Asymmetric / ø60mm

63471

Design: O/M + Bartenbach GmbH

Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.

Accurate reflector for a defined and controlled beam of light, achieving maximum efficiency.


Fitting accessories for different applications are available.

LED CRI>80 / >50.000h, L80/B10 2-step MacAdam / Power supply included. IP20 | 230Vac | 50/60Hz






1000K	Light Source	Luminaire
Power	5,9W	7,4W
Flux	740lm	630lm
Efficiency	125lm/W	85lm/W
LOR	-	85%
UGR	-	-



Beam angle Asymmetric Application

Weight

mm 



## Finishes

O .01 White / RAL 9010 ● .02 Black / RAL 9005

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class E Model Identifier 4053560100