



One **Square**

3,1W / 240lm / 4000K / DALI / Flood 56° / 45×45mm

63507

Design: O/M + Bartenbach GmbH

Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.


Lightcore optics for defined and perfectly controlled beam of light.

Fitting accessories for different applications are available.

LED CRI>80 / >50.000h, L80/B10 2-step MacAdam / Power supply included. IP20 | 230Vac | 50/60Hz



1000K	Light Source	Luminaire		
Power	3,1W	4W		
Flux	280lm	240lm		
Efficiency	90lm/W	60lm/W		
LOR	-	86%		
UGR	-	<16		



Beam angle Flood 56°


Application



Weight 0,22Kg

I	7	mm			

△ 37x37



Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class G Model Identifier 4053560313L