



3,1W / 240lm / 4000K / On/Off / Flood 56° / ø39mm

63535

Design: O/M + Bartenbach GmbH

Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.


Lightcore optics for defined and perfectly controlled beam of light.

Recessing accessory supplied separately.

LED CRI>80 / >50.000h, L80/B10 2-step MacAdam / Power supply included. IP20 | 230Vac | 50/60Hz



<b>4000K</b>	Light Source	Luminaire
Power	3,1W	4W
Flux	280lm	240lm
Efficiency	90lm/W	60lm/W
LOR - 86		86%
UGR	-	<16




Beam angle Flood 56°

Application



Weight

mm		



## Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

Mandatory

59042 Trimless accessory (12.5mm ceilings)

140×18mm

59043 Trimless accessory (15mm ceilings)

140×20mm

59044 Trimless accessory (25mm ceilings)

140×30mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class G Model Identifier 4053560313L