

3,1W / 240lm / 4000K / DALI / Flood 56° /  
ø39mm

63537



Design: O/M + Bartenbach GmbH  
Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.  
Lightcore optics for defined and perfectly controlled beam of light.  
Recessing accessory supplied separately.

LED CRI>80 / >50.000h, L80/B10  
2-step MacAdam / Power supply included.  
IP20 | 230Vac | 50/60Hz



**4000K**

**Light Source**

**Luminaire**


**Power** **3,1W** **4W**

**Flux** **280lm** **240lm**

**Efficiency** **90lm/W** **60lm/W**

**LOR** **-** **86%**

**UGR** **-** **<16**



**Beam angle**  
**Flood 56°**

**Application**

**Weight**

**mm**

**Finishes**

- .01 White / RAL 9010**
- .02 Black / RAL 9005**

**Mandatory**

**59042** Trimless accessory (12.5mm ceilings)

140x18mm

**59043** Trimless accessory (15mm ceilings)

140x20mm

**59044** Trimless accessory (25mm ceilings)

140x30mm

**Optional**

**59083** Removal tool

For the specific supply of "DALI 2" drivers, please contact:  
[support@om-light.com](mailto:support@om-light.com)

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)

**Data according to regulations**

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU

supplemented by 2021/340/EU Energy Consumption Labelling

Ordinance. This product contains a light source of efficiency class G  
Model Identifier 4053560313L

