



One **Square Trimless**

3,1W / 200lm / 2700K / DALI / Medium 40° / 39x39mm

63552

Design: O/M + Bartenbach GmbH

Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.


Lightcore optics for defined and perfectly controlled beam of light.

Recessing accessory supplied separately.

LED CRI>90 / >50.000h, L80/B10 2-step MacAdam / Power supply included. IP20 | 230Vac | 50/60Hz



2700K	Light Source	Luminaire
Power	3,1W	4W
Flux	260lm	200lm
Efficiency	84lm/W	50lm/W
LOR	-	77%
UGR	-	<10




Beam angle Medium 40°

Application



Weight

mm



Finishes

O .01 White / RAL 9010 ● .02 Black / RAL 9005

Mandatory

59048 Trimless accessory (12.5mm ceilings)

140×18mm

59049 Trimless accessory (15mm ceilings)

140×20mm

59050 Trimless accessory (25mm ceilings)

For the specific supply of "DALI 2" drivers, please contact:

The cutout dimensions are for plasterboard ceilings. For other type of $material\ please\ contact: support@om-light.com$

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class G Model Identifier 4053560312L