

3,1W / 200lm / 3000K / On/Off / Medium
40° / 39x39mm

63554



Design: O/M + Bartenbach GmbH
Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.
Lightcore optics for defined and perfectly controlled beam of light.
Recessing accessory supplied separately.

LED CRI>90 / >50.000h, L80/B10
2-step MacAdam / Power supply included.
IP20 | 230Vac | 50/60Hz



3000K

Light Source

Luminaire

Power

3,1W

4W

Flux

260lm

200lm

Efficiency

84lm/W


50lm/W

LOR

77%

UGR

<10




Beam angle
Medium 40°



Weight

mm



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Mandatory

59048 Trimless accessory (12.5mm ceilings)

140x18mm

59049 Trimless accessory (15mm ceilings)

140x20mm

59050 Trimless accessory (25mm ceilings)

140x30mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU

supplemented by 2021/340/EU Energy Consumption Labelling

Ordinance. This product contains a light source of efficiency class G

Model Identifier 4053560290L