

# O/M

## One Adjustable

5,6W / 215lm / 4000K / On/Off / Spot 15° /  
ø60mm

63570



Design: O/M + Bartenbach GmbH  
Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.  
Orientable by 20° horizontal rotation.  
Spot-lens with individual complex surface rips to provide a focal light and an extremely narrow beam.

LED CRI>80 / >50.000h, L80/B10  
2-step MacAdam / Power supply included.  
IP20 | 230Vac | 50/60Hz



4000K

Light Source

Luminaire

Power

5,6W

7W

Flux

480lm

215lm

Efficiency

86lm/W


31lm/W

LOR

45%

UGR

<10



Beam angle  
Spot 15°

Application

Weight  
0,58Kg


mm

Ø54

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com



Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class G  
Model Identifier 4053560313H