



One **Adjustable**

5,6W / 430lm / 4000K / DALI / Medium 40° / ø60mm

63573

Design: O/M + Bartenbach GmbH

Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.


Orientable by 20° horizontal rotation.

Accurate reflector for a defined and controlled beam of light, achieving maximum efficiency.

LED CRI>80 / >50.000h, L80/B10 2-step MacAdam / Power supply included. IP20 | 230Vac | 50/60Hz



1000K	Light Source	Luminaire	
Power	5,6W	7W	
Flux	490lm	430lm	
Efficiency	88lm/W	61lm/W	
LOR	-	88%	
UGR	-	<19	




Beam angle Medium 40°

Application



Weight 0,53Kg

mm		Q 054



Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class G Model Identifier 4053560313H