



One

Surface/Pendant

9,8W / 550lm / 2700K / DALI / Spot 15° / ø85mm

63593




Design: O/M + Bartenbach GmbH Surface/Pendant luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.

Spot-lens with individual complex surface rips to provide a focal light and an extremely narrow beam. Fitting accessories ordered separately

LED CRI>90 / >50.000h, L80/B10 2-step MacAdam / Power supply included. IP20 | 230Vac | 50/60Hz



2700K	Light Source	Luminaire
Power	9,8W	12,3W
Flux	955lm	550lm
Efficiency	97lm/W	45lm/W
LOR	-	58%
UGR	-	<10




Beam angle Spot 15°

Application



Weight 0.58Kg

7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
7	
//	
7	
7	
7	
7	



Finishes

O .01 White / RAL 9010

● .02 Black / RAL 9005

Mandatory

59051 Accessory for pendant installation ø80x35mm

For the specific supply of "DALI 2" drivers, please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F Model Identifier 2053560245H