

27W / 1960lm / 3000K / DALI / Flood 52° /
1211mm

63962



Design: O/M + Bartenbach GmbH
Surface or pendant luminaire with housing made of aluminium with electrostatic 100% polyester paint with textured finish.

Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured finish.


Housing and perforated cover plate made of aluminium with textured-paint finish. With the latest Bartenbach GmbH technology, inVision35 is a discreet solution, that can use great light distribution and visual comfort from a nearly invisible source.

Fitting accessories for pendant version ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam
Power supply included.
IP20 | 230Vac | 50/60Hz



	3000K	Light Source	Luminaire
Power	27W	32,9W	
Flux	2580lm	1960lm	
Efficiency	96lm/W	60lm/W	
LOR	-	76%	
UGR	-	<13	



Beam angle
Flood 52°



Weight
2,5Kg

1211 mm

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Mandatory

54036 Pendant direct fitting accessory
56051 Clear Base DALI
ø60x35mm

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com

