

23W* / 1360lm* / 2200K-5000K / DALI /
Medium 31° / 615mm

63988



Design: O/M + Bartenbach GmbH
Recessed luminaire with housing made of aluminium with electrostatic 100% polyester paint with textured finish.

Aluminium anodised end caps with electrostatic 100% polyester paint with textured-finish. Housing and perforated cover plate made of aluminium with textured-paint finish. With the latest Bartenbach GmbH technology, inVision45 is a discreet solution, that can use great light distribution and visual comfort from a nearly invisible source. Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
DALI DT8.
IP20 | 230Vac | 50/60Hz




2200K-5000K

Light Source

Luminaire

Power	23W*	28W*
Flux	1880lm*	1360lm*
Efficiency	82lm/W	48lm/W
LOR	-	72%
UGR	-	<10



Beam angle
Medium 31°



Weight
1,3Kg

mm

47x605

Finishes

- .01** White / RAL 9010
- .02** Black / RAL 9005

Mandatory

51027 Recessed fitting accessory

O/M recommends that any false ceilings intended for recessed products should be installed only after the products to be used have been chosen. The same applies when preparing openings for this type of product. O/M recommends reinforcing false ceilings close to any such openings, in accordance with the characteristics of the product to be recessed. The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

