

45+90W / 2300+4600lm / 3000K / On/Off /  
Diffuse Direct/ Indirect / 2821mm

64174



Design: Eduardo Souto de Moura

MGB Pendant Indirect module with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with textured electrostatic 100% polyester paint.

Frosted acrylic diffuser with user friendly clipping system.

Steel end caps with textured electrostatic 100% polyester paint.

Frosted acrylic diffuser for direct light and indirect light.

Fitting accessories supplied separately.



LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam

Power supply included.

IP20 | 230Vac | 50/60Hz



| LED        | 3000K | Light Source | Luminaire   |
|------------|-------|--------------|-------------|
| Power      |       | 45+90W       | 65+130W     |
| Flux       |       | 5750+11500lm | 2300+4600lm |
| Efficiency |       | 128lm/W      | 35lm/W      |
| LOR        |       | -            | 40%         |
| UGR        |       | -            | <25         |



### Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .03 Grey / RAL 9006

### Mandatory

54034 Clear base

Ø60x35mm

54080 Aluminium base

Ø60x37mm