



Sky Recessed

66W / 9030lm / 3000K / On/Off / Diffuse /
ø850mm

64560

Design: O/M

Recessed luminaire made of aluminium body with electrostatic 100% polyester paint with textured-finish suitable for adverse climate conditions.


Frosted acrylic diffuser with perfect light uniformity.
Recessing accessories supplied separately.



LED: CRI>80 />50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP43 | 230Vac | 50/60Hz



LED	3000K	Light Source	Luminaire
Power	66W	77,6W	
Flux	11130lm	9030lm	
Efficiency	169lm/W	116lm/W	
LOR	-	81%	
UGR	-	<25	





Beam angle
Diffuse

Application

Weight
8,5Kg

mm Ø 0857



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .03 Grey / RAL 9006

Mandatory

59079 Recessed fitting accessory
Ø858x958x134mm

Recessed accessory for different ceiling heights under request

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains light sources of efficiency class D
Model Identifier 89603018