

66W / 9570lm / 4000K / On/Off / Diffuse /
ø850mm

64566


Design: O/M
 Recessed luminaire made of aluminium body with electrostatic 100% polyester paint with textured-finish suitable for adverse climate conditions.
 Frosted acrylic diffuser with perfect light uniformity.
 Recessing accessories supplied separately.



LED: CRI>80 />50.000h, L80/B10 / 3-step MacAdam
 Power supply included.
 IP43 | 230Vac | 50/60Hz



LED	4000K	Light Source	Luminaire
Power	66W	77,6W	
Flux	11800lm	9570lm	
Efficiency	179lm/W	123lm/W	
LOR	-	81%	
UGR	-	<25	





Beam angle
 Diffuse

Application

Weight
 8,5Kg

mm Ø 0857



Ø850

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .03 Grey / RAL 9006

Mandatory

59079 Recessed fitting accessory
 Ø858x958x134mm

Recessed accessory for different ceiling heights under request

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
 supplemented by 2021/340/EU Energy Consumption Labelling
 Ordinance. This product contains light sources of efficiency class C
 Model Identifier 89603019