

66W / 9030lm / 3000K / On/Off / Diffuse /  
ø850mm

64584



Design: O/M

Pendant luminaire made of aluminium body with electrostatic 100% polyester paint with textured-finish suitable for adverse climate conditions.

Frosted acrylic diffuser with perfect light uniformity. Suspension system with millimetric height adjustment ordered separately.

Power supply base made of clear polycarbonate, clear power cable (3x0,75mm<sup>2</sup>) and steel suspension cables (1,2mm) with millimetric height adjustment system supplied separately.

Accessories supplied separately.

LED: CRI&gt;80 /&gt;50.000h, L80/B10 / 3-step MacAdam

Power supply included.

IP43 | 230Vac | 50/60Hz



**LED** 3000K

**Light Source**

**Luminaire**


**Power** **66W** **77,6W**

**Flux** **11130lm** **9030lm**

**Efficiency** **169lm/W** **116lm/W**

**LOR** **-** **81%**


**UGR** **-** **<25**



**Beam angle**  
**Diffuse**

**Application**

**Weight**  
**8,5Kg**



**Finishes**

- .01 White / RAL 9010**
- .02 Black / RAL 9005**
- .03 Grey / RAL 9006**

**Mandatory**

**59080** Pendant fitting accessory

**54034** Clear Base

ø60x35mm

**Data according to regulations**

2019/2020/EU supplemented by 2021/341 |2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains light sources of efficiency class D  
Model Identifier 89603018