

21W / 2320lm / 4000K / On/Off / Diffuse /
ø400mm

64588



Design: O/M

Pendant luminaire made of aluminium body with electrostatic 100% polyester paint with textured-finish suitable for adverse climate conditions.

Frosted acrylic diffuser with perfect light uniformity. Suspension system with millimetric height adjustment ordered separately.

Power supply base made of clear polycarbonate, clear power cable (3x0,75mm²) and steel suspension cables (1,2mm) with millimetric height adjustment system supplied separately.

Accessories supplied separately.


LED: CRI>80 / >50.000h, L80/B10 / 3-step MacAdam

Power supply included.

IP43 | 230Vac | 50/60Hz



4000K


Light Source**Luminaire****Power****21W****26W****Flux****3430lm****2320lm****Efficiency****163lm/W****89lm/W****LOR****-****68%****UGR****-****<25**

Beam angle
Diffuse

Application

Weight
4,5Kg

mm

**Finishes**


- .01 White / RAL 9010**
- .02 Black / RAL 9005**
- .03 Grey / RAL 9006**

Mandatory

59080 Pendant fitting accessory

54034 Clear Base

ø60x35mm

**Data according to regulations**

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class C
Model Identifier 89603356