




Design: O/M + Eduardo Souto de Moura  
 Outdoor luminaire in aluminium body with anti-corrosion treatment and textured electrostatic 100% polyester paint finish.  
 Clear glass diffuser.  
 Asymmetrical aluminium reflector with 97% reflection, low luminance level and low UGR level.  
 Fitting accessory available separately.

\*Polycarbonate clear diffuser (IK10) available under request.

LED CRI>90 / >50.000h, L80/B10  
 2-step MacAdam / power supply included.  
 IP66 | 230Vac | 50/60Hz



| LED        | 2700K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power      |       | 6,2W         | 7,8W      |
| Flux       |       | 670lm        | 240lm     |
| Efficiency |       | 108lm/W      | 31lm/W    |
| LOR        |       | -            | 36%       |
| UGR        |       | -            | -         |




Beam angle  
 Elliptical transverse

Application



Weight  
 3Kg



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .33 Graphite Black
- .34 Rust

Optional

59081 Tua Fitting accessory

For the specific supply of "DALI 2" drivers, please contact:  
[support@om-light.com](mailto:support@om-light.com)