



## Go Square

6,7W / 3,4W / 855lm / 425lm / 3000K / Flood 48° / 75x75mm

64813

Design: O/M

Ceiling-recessed luminaire made of aluminium die-


cast.

Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10 3-step MacAdam / Power supply not included IP44 | 200mA / 100mA




	Light Source	Luminaire
Power	6,7W / 3,4W	6,7W / 3,4W
Flux	1055lm / 530lm	855lm / 425lm
Efficiency	157lm/W	128lm/W
LOR	-	81%
UGR	-	<19



Beam angle
Flood 48°

Application

mm ∠Z765x65



## Finishes

O .04 Matt White

• .05 Matt Black

Mandatory

**59101** Driver On/Off [200mA]

147×43×30mm

**59100** Driver On/Off [100mA]

110×40×21mm

**59103** Driver DALI [200mA]

144×30×21mm

**59102** Driver DALI [100mA]

144×30×21mm

59105 Driver PhaseCut [180mA]

102×49×29mm

59104 Driver PhaseCut [100mA]

122×41×23mm

**59107** Driver 1-10V [200mA]

130×30×20mm

**59106** Driver 1-10V [120mA]

130×30×20mm

Optional

**59151** Louvre

ø35x4mm

59152 Elliptical diffuser

ø35x4mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

The 5-year guarantee applies only when the luminaire and driver are supplied together.

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class E Model Identifier BXRE-30G10FB-C-83