


43W / 4080lm / 4000K / DALI / Wide flood  
76° / 2408mm

64913




Design: Eduardo Souto de Moura  
 Surface luminaire with tubular semi frosted PMMA body with 70mm diameter.  
 Clear polycarbonate end caps with marked installation angles.  
 Linear lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.  
 Equipped with 2m cable (5x0.75 mm<sup>2</sup>).  
 Fitting accessories ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam  
 Power supply included.  
 IP44 | 230Vac | 50/60Hz



LED	4000K	Light Source	Luminaire
Power	43W	49,9W	
Flux	6000lm	4080lm	
Efficiency	142lm/W	82lm/W	
LOR	-	68%	
UGR	-	<16	



Beam angle  
 Wide flood 76°



Weight

2408 mm

Finishes

.01 White / RAL 9010

Mandatory

59163 Surface fitting accessor (>1600mm)

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
 supplemented by 2021/340/EU Energy Consumption Labelling  
 Ordinance. This product contains light sources of efficiency class E  
 Model Identifier 4053560084

